

Introducing the new model  
**KH125T-36 (ADV125)**







Full Body



Back Light



White Board



Default Board



Modern Function



White



Yellow



Grey



Blue



Red



Black

\*Any color customer can order to customize



Model	KH125T-36 (ADV125)	
	Standard	Flagship
Version		
Length (mm)		2073
Width (mm)		735
Height (mm)		1262
Wheel base (mm)		1324
Max speed (km/h)		105
Max power (kW/r/min)		10.7/8500
Max torque (N·m/r/min)		12.5/6500
Fuel tank (L)		9.3L
Fuel consumption(L/100km)		2.2
Total mileage (KM)		420KM
Displacement (cc)		125
Ground clearance (mm)		158
Main seat height (mm)		775
Net weight (Kg)		150
Tire specifications	Front wheel 110/80-14 ; rear wheel 130/70-13	
Battery model and specification	12V9Ah	12V11.2Ah (High-performance fast charge and discharge)
<b>Vehicle configuration</b>		
T-box	-	1
shock absorption	Front and upright double shock absorber, Rear double shock absorber	Front and upright double shock absorber , Rear double airbag shock absorption
ABS	Front and rear dual channel ABS	
Braking type	Front disc and back disc	
Headlight light	Four lens LED (AFS)	
Taillight	LED	LED(with ESS emergency)
Engine start and stop	-	1
EVAC	-	1
Fuel supply method	EFI	
Engine cooling	Water-cooled	
Lock type	Intelligent central control	
Speedometer	7 inch LCD	7 inch TFT with TBOX
Driving recorder	-	1
Front and rear cameras	-	1
Phone APP	-	1
Tire pressure alarm	-	1
Navigation screencast	-	1
Hybrid indicator	-	1
USB charging port	1	
Side stand shut down	1	
Container quantity	CBU 36units/1X40HQ'; CKD 72units/1X40HQ'	

EVAC:

1- Technical Introduction:

When refueling, the speed reaches more than 2000 RPM, the program intelligent detection, control ISG magneto to provide electric power to the engine,

about 10 seconds

2- Technical Advantages:

Instant acceleration performance is improved, climbing performance is improved, fuel consumption and pollutant emissions are reduced

